

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
10 November 2005 (10.11.2005)

PCT

(10) International Publication Number  
**WO 2005/106265 A1**

(51) International Patent Classification<sup>7</sup>: **F16C 19/50**

(21) International Application Number:  
PCT/IL2005/000465

(22) International Filing Date: 3 May 2005 (03.05.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/567,444 4 May 2004 (04.05.2004) US

(71) Applicant and

(72) Inventor: **BEZYAIKO**, Natan [IL/IL]; 16 Baruch Karo  
Street, 68203 Jaffa (IL).



(74) Agents: **WATERMAN, HADASSA** et al.; G.E. Ehrlich  
(1995) LTD., 11 Menachem Begin Street., 52 521 Ramat  
Gan (IL).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD FOR MULTI ORBITAL ENGAGEMENT OF SURFACES BY FREE ROLLING BODIES AND MULTI ORBITAL DEVICES BASED ON THIS METHOD



(57) Abstract: The present invention provides a new bearing device of free rolling parts. According to the basic embodiment the bearing device is comprised of: an inner race, an outer race, two rows of rolling parts wherein each rolling part is in not in a contact with two adjacent rolling parts in the same row and in contact with rolling parts of at least one adjacent row and/or with the surface of one of the races. The bearing structure is designed to create orbital eccentricity between the inner race and the outer race. When a load is applied on said bearing it is equally distributed over all rolling parts. Furthermore, the load applied on said bearing decrease the orbital eccentricity, wherein minimum limit of orbital eccentricity is maintained through the working process. The device engagement of rolling parts is slack-free.



**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*